

Products Features

- ▶ Using high density LEDs.
- ▶ High intensity and uniformity.
- ▶ Using special coated mirror.
- ▶ Suitable for scratch inspection of smooth surface.


Customization

- Dimensions
- Color
- Power
- Cable length
- Mounting
- Connector


Applications the light be used for

- Laser mark inspection of wafer.
- Marked charaters inspection of metal, bearing, can.
- QR code inspeciton of metal and glass.
- LCD defects inspection.


Model Description



Structure



Components



Parameter

Item	Model	Power consumpition Red Color	Power consumpition (W,B,G)	Option	Extension cable	Recommended Controller
1	SBS-CL40-X	24V/1.73W	24V/2.30W	Diffuser	1m/3m/5m	SBS-AC24XX-X (Analog controller) SBS-DC24XX-X (Digital controller) SBS-ODC48XX-X (Strobe controller)
2	SBS-CL50-X	24V/2.30W	24V/3.74W	Diffuser	1m/3m/5m	
3	SBS-CL60-X	24V/3.45W	24V/5.18W	Diffuser	1m/3m/5m	
4	SBS-CL70-X	24V/4.89W	24V/7.20W	Diffuser	1m/3m/5m	

Dimensions(mm)

SBS-CL40-X	SBS-CL50-X
SBS-CL60-X	SBS-CL70-X